



ELEKTRAX - LUBRICANTS



PREMIUM ENGINE OIL SAE 10W40

Performance Standard : API SN/CI-4

ELEKTRAX 10W40 is an extra high performance petrol engine oil that provides excellent lubrication of today's petrol engines promoting extended engine life. As a result, this product meets or exceeds the specifications of virtually all major European and American engine manufacturers. This extra high performance has been proven in the field in a wide variety of industries, applications, and mixed fleets.

Features and Benefits

10W40 is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in modern diesel and gasoline engines as well as older models. The key benefits include:

Features	Advantages and Benefits
High thermal and oxidation stability	Reduced sludge build-up, deposits and viscosity increase
TBN reserves	Deposit control and acid neutralization
Stay-in-grade shear stability	Wear protection and viscosity control
Excellent low temperature properties	Start-up wear protection
Meets demanding specifications of key OEMs	One engine oil for mixed fleet operations

Applications

- ✦ High-performance engine oil for all types of cars where this viscosity is recommended
- ✦ This includes high-performance turbo-charged, supercharged gasoline multi-valve fuel injected engines found in passenger cars, SUVs, light vans and trucks.



ELEKTRAX - LUBRICANTS



PREMIUM ENGINE OIL SAE 10W40

Performance Standard : API SN/CI-4

Technical Specification :

TEST PARAMETERS	TEST METHODS	RESULT
DENSITY @15°C (Kg/L)	ASTM D4052	0.8646
VISCOSITY @ 40°C (cst)	ASTM D445	93.09
VISCOSITY @ 100°C (cst)	ASTM D445	14.42
VISCOSITY INDEX	ASTM D 2270	161
FLASH POINT (°C)	ASTM D92	214
POUR POINT (°C)	ASTM D97	-45

Handling health & Safety :

Lubricants consisting of highly refined mineral oils with specification additives. In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding can contact with the skin.

Prevent any splashing, and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off the used oil correctly; don't pour down drains, into watercourses or the soil.